# RESTAURANT EQUIPMENT WAREHOUSE

ALL FLYER PRICING DOES NOT INCLUDE FREIGHT DELIVERY, INSTALLATION, OR TAXES.

#### 05/28/2021

#### CONVECTION OVEN, ELECTRIC Duke Manufacturing Model E101-E

Convection Oven, electric, single-deck, standard depth, thermostatic controls, with 26" high legs, stainless steel front, painted cabinet, NSF, cETLus



## CONVECTION OVEN, ELECTRIC Duke Manufacturing Model E102-E

Convection Oven, electric, double-deck, standard depth, thermostatic controls, with 8" high stainless steel legs & adjustable stainless steel feet, stainless steel front, painted steel cabinet, 50/50 stainless steel independent doors, (2) windows, (5) racks & (13) rack positions per deck, porcelain interior, (200°-500°F), 60 minute dial timer with buzzer & (2) speed fan, NSF, cETLus



#### CONVECTION OVEN, GAS Duke Manufacturing Model E101-G

Convection Oven, gas, singledeck, standard depth, thermostatic controls, with 26" high legs, stainless steel front, painted cabinet, NSF, CSA STAR, CSA FLAME, ENERGY STAR®



### CONVECTION OVEN, GAS Duke Manufacturing Model E102-G

Convection Oven, gas, double-deck, standard depth, thermostatic controls, with 8" high stainless steel legs & adjustable stainless steel feet, stainless steel front, painted steel cabinet, 50/50 stainless steel independent doors, (2) windows, (5) racks & (13) rack positions per deck, porcelain interior, (200°-500°F), 60 minute dial timer with buzzer & (2) speed fan, ENERGY STAR®



#### CONVECTION OVEN, GAS Atosa USA, Inc. Model ATCO-513B-1

CookRite Convection Oven, gas, single-deck, bakery depth, 50/50 dependent doors with double pane thermal tempered glass, 150° to 500° F temperature range, digital controller with Cook 'n' Hold, 2-speed-fan with adjustable cool down mode, interior lighting, (5) wire racks, removable13-position rack guides, door interlock switches, automatic pilot system with safety shut-off, enamel interior, stainless steel exterior, includes: leg kit with (4) stainless steel legs & locking casters, 115v/60/1-ph, 8.5 amps, 46,000 BTU/HR, cETLus, ETL-Sanitation



#### CONVECTION OVEN, GAS Atosa USA, Inc. Model ATCO-513B-2

CookRite Convection Oven, gas, double-deck, bakery depth, 50/50 dependent doors with double pane thermal tempered glass, 150° to 500° F temperature range, digital controller with Cook 'n' Hold, 2-speed-fan with adjustable cool down mode, interior lighting, (5) wire racks per oven, removable13-position rack guides per oven, door interlock switches, automatic pilot system with safety shut-off, enamel interior, stainless steel exterior, includes: leg kit with (4) stainless steel legs & locking casters, (2) 115v/60/1-ph, (2) 8.5 amps, 92,000 BTU/HR, cETLus, ETL-Sanitation



### CONVECTION OVEN, ELECTRIC Royal Range of California Model RECO-1

Convection Oven, electric, single-deck, standard depth, accommodates full size sheet pans, electric thermostat adjustable from 150-500°F, (5) chrome plated racks standard with (11) positions, porcelain coated interior, dual stainless steel doors with glass viewing window on right, stainless steel front, sides & top, 9.0kW, cETLus, ETL-Sanitation, Made in USA



#### CONVECTION OVEN, GAS Royal Range of California Model RCOS-1

Convection Oven, gas, single-deck, standard depth, thermostatic controls, temp range 150°F - 500°F, electronic ignition, 2-speed fan, porcelain interior, dual stainless steel doors with glass viewing window on right, stainless steel front, sides & top, legs, 70,000 BTU, cETLus, ETL-Sanitation, NSF, Made in USA



#### CONVECTION OVEN, ELECTRIC Royal Range of California Model RECO-2

Convection Oven, electric, double-deck, standard depth, accommodates full size sheet pans, electric thermostat adjustable from 150-500°F, (5) chrome plated racks standard with (11) positions, porcelain coated interior, dual stainless steel doors with glass viewing window on right, stainless steel front, sides & top, (2) 9.0kW, cETLus, ETL-Sanitation, Made in USA



#### CONVECTION OVEN, GAS Royal Range of California Model RCOS-2

Convection Oven, gas, double-deck, standard depth, thermostatic controls, temp range 150°F - 500°F, electronic ignition, 2-speed fan, porcelain interior, dual stainless steel doors with glass viewing window on right, stainless steel front, sides & top, legs, 140,000 BTU, cETLus, ETL-Sanitation, NSF, Made in USA

